

CH8930

Code 6600

***Approved Aircraft Paint Stripper Phenolic, Neutral.
Quick Removal of Epoxy, Polyurethane &
Difficult to Remove Coatings***

DESCRIPTION

CH8930 is a thickened non-flammable, neutral phenolic paint stripper for brush or spray application. CH8930 will remove most difficult to remove coatings such as epoxy, polyurethane, enamels and primers.

CHARACTERISTICS

CH8930 is a heavy bodied, viscous material which will cling to vertical and inverted surfaces. Amber colour, low odour, slow evaporation rate and extended working life.

Non-corrosive to aluminium, cadmium, high strength steel and all aircraft metal surfaces.

APPROVALS

CH8930 has been tested and qualified to the following specifications.

- Boeing D6 17487
- AMS 1375
- Douglas CSD*1, Type III
- USAF MIL-R-81294B
- GPC-R-49 (RAAF K55)

APPLICATION

Precaution – CH8930 is damaging to acrylics, most plastics and composites. Avoid contact to prevent damage.

Clean any soiled or oily surfaces prior to stripping. Mask off all perspex, plastic and rubber components. To avoid unnecessary evaporation carry out stripping operation away from direct sunlight or wind.

Apply CH8930 by spray or brush. For spraying, use a Graco barrel pump or equivalent. Once paint film has blistered, agitate area with stiff bristle brush if necessary and then rinse off with high pressure water or scrape and rinse off.

SAFETY PRECAUTIONS

CH8930 contains strong solvents and phenol, therefore care must be taken and contact with skin and eyes should be avoided. Avoid breathing vapour or spray mist. The operator is advised to wear protective clothing, gloves and eye shields.

... /2

FIRST AID

If poisoning occurs contact a doctor or Poisons Information Centre. If swallowed give 1-3 cups of olive oil or other cooking oil or milk. Get to a doctor or hospital quickly. If spilt on the skin remove any contaminated clothing swab repeatedly with glycerin, PEG (polyethylene glycol) or PEG - methylated spirit mixture or if necessary methylated spirit alone. If in eyes hold open and flood with water for 15 minutes and see a doctor as soon as possible. Remove from contaminated area. Apply artificial respiration if not breathing.

PACKAGING

CH8930 is packed in 20 litre and 200 litre steel drums.

WARRANTY – All statements, information and data presented herein are believed to be accurate and reliable but are not to be taken as a guarantee, expressed or implied, for which seller assumes legal responsibility and they are offered solely for your consideration, investigation and verification. Statements or suggestions concerning possible use of this product are made without representation or warranty that any such use is free of patent infringement and are not recommendations to infringe on any patent.

Created 10 October 2008 Date Printed 14/04/2010 1:42 PM



CALLINGTON HAVEN PTY LTD
Incorporated in New South Wales
ACN 000 632 404 ABN 28 000 632 404
30 South Street Rydalmere NSW 2116
PO Box 144 Rydalmere NSW BC 1701 Australia
T: (61-2) 9898 2788 F: 9684 4215
E: enquiries@calhaven.com.au W: www.callingtonhaven.com

